

**STANDARD FEATURES**

Available in 3 1/2" dial sizes, Regal pressure gauges are liquid fillable and field convertible for panel mounting. Both zero and span adjustments are standard. The gauge is available dry, liquid-filled weatherproof or hermetically sealed.

- Designed for safety and long life
- All stainless, all-welded construction for long life
- ASME Grade 1A, 1% accuracy full scale
- No stop pin to mask false zero reading – ensures safety and process control
- 5-year limited warranty



**PRESSURE RANGES**

CODE NO.	DIAL RANGES	FIGURE INTERVALS	SMALLEST GRADUATION
PC	0-15 psi	1 psi	.25 psi
PD	0-30 psi	5 psi	.5 psi
PE	0-60 psi	10 psi	1 psi
PF	0-100 psi	10 psi	1 psi
PG	0-160 psi	20 psi	2 psi
PH	0-200 psi	20 psi	2 psi
PJ	0-300 psi	50 psi	5 psi
PK	0-400 psi	50 psi	5 psi
PM	0-600 psi	100 psi	10 psi
PO	0-800 psi	100 psi	10 psi
PP	0-1000 psi	100 psi	10 psi
PR	0-1500 psi	200 psi	10 psi
PS	0-2000 psi	200 psi	20 psi
PT	0-3000 psi	500 psi	20 psi
PV	0-5000 psi	500 psi	50 psi
PY	0-10,000 psi	1000 psi	100 psi
PZ	0-15,000 psi	3000 psi	100 psi

**VACUUM RANGES**

CODE NO.	DIAL RANGES	FIGURE INTERVALS	SMALLEST GRADUATION
VC	30"-0 Hg. Vac	3"	.2"

**BOURDON TUBE AND SOCKET**

CATALOG NO.	BOURDON TUBE & SOCKET MATERIAL	DIAL SIZE	GAUGE TYPE	OPTIONAL CASE STYLE	
				LOWER CONNECT	BACK CONNECT
BA13	Brass/Bronze <sup>(1)</sup>	3 1/2"	Dry	"X" Style SS Back Flanged	"X" Style SS
BS13			Herm. Sealed		Back Flanged
BY13			Liquid Fill		"U" Style SS
BA43	316 SS		Dry		U-Clamp
BS43			Herm. Sealed		"V" Style SS
BY43			Liquid Fill		Front Flanged

**COMPOUND RANGES**

CODE NO.	DIAL RANGES	FIGURE INTERVALS	SMALLEST GRADUATION
CA	30"-0- 15 psi	5" & 3 psi	.5"/2 psi
CB	30"-0- 30 psi	10" & 5 psi	1"/5 psi
CC	30"-0- 60 psi	10" & 10 psi	1"/1 psi
CD	30"-0-100 psi	30" & 10 psi	2"/1 psi
CE	30"-0-150 psi	30" & 20 psi	5"/2 psi
CF	30"-0-200 psi	30" & 20 psi	5"/2 psi
CG	30"-0-300 psi	30" & 50 psi	10"/5 psi
CI	30"-0-600 psi	30" & 100 psi	10"/10 psi

**NOTES:**

1. Brass/Bronze maximum range is 1000 psi.

**HOW TO ORDER**

**B A 4 3 Y P F 4 L W ( )**

1. Basic 4-digit Catalog No. From Table Above \_\_\_\_\_
2. Stainless Steel Case Style "Y" Standard \_\_\_\_\_
3. Range Code From Range Tables Above \_\_\_\_\_
4. Thread Size: 4 = 1/4 Npt Male (only) \_\_\_\_\_
5. Connection Location: L = Lower (Bottom), R = Back (Rear) \_\_\_\_\_
6. Dial Color: W = White \_\_\_\_\_
7. If Any Gauge Options Are Desired – Specify Option Code(s) From Page 37 \_\_\_\_\_