

**STANDARD FEATURES**

- Available in 63mm size
- Cast brass case and brass plated plastic ring with plastic window
- ¼ NPT lower and back connection available
- Dual scale dials with kPa in blue (outer scale); psi in black (inner scale); on white background



BY12JPV4LW

BY12JPE4CW

**CATALOG NUMBERS**

Dial Size	63mm	
	Back	Bottom
Connection Location	Back	Bottom
Connection NPT	¼	¼
Range (psi & kPa)		
30"/0/ vac. and -100/0 kPa	BY12JVC4CW	BY12JVC4LW
30"/0/30 psi and -100/0/200 kPa		
30"/0/60 psi and -100/0/400 kPa	BY12JCC4CW	BY12JCC4LW
30"/0/150 psi and -100/0/1000 kPa		
0-15 psi and 100 kPa		
0-30 psi and 200 kPa	BY12JPD4CW	BY12JPD4LW
0-60 psi and 400 kPa	BY12JPE4CW	BY12JPE4LW
0-100 psi and 700 kPa	BY12JPF4CW	BY12JPF4LW
0-160 psi and 1100 kPa	BY12JPG4CW	BY12JPG4LW
0-200 psi and 1400 kPa		
0-300 psi and 2100 kPa	BY12JPJ4CW	BY12JPJ4LW
0-600 psi and 4200 kPa		
0-1000 psi and 7000 kPa	BY12JPP4CW	BY12JPP4LW
0-2000 psi and 14,000 kPa		
0-3000 psi and 21,000 kPa	BY12JPT4CW	BY12JPT4LW
0-5000 psi and 35,000 kPa	BY12JPV4CW	BY12JPV4LW
0/10,000 psi and 70,000 kPa	BY12JPY4CW	BY12JPY4LW

To order: specify 10-digit "catalog number" from above table.

**GAUGE DIMENSIONS BY12J**

Lower Connection Gauge Size/Type		A	B	C	D-¼	E	F	
63 mm	BY12J	Inch	2.60	1.50	2.20	0.41	1.21	2.44
		mm	66	38	56	10	31	62
Back Connection Gauge Size/Type		A	B	F	G			
63 mm	BY12J	Inch	2.60	1.50	2.44	2.46		
		mm	66	38	62	62		

